



# technical specifications


|                            |  |
|----------------------------|--|
| Product Name               | Academy  |
| Product Description        | Heavy Contract Carpet Tiles  |
| Pile Yarn Description      | 85% Polypropylene 15% Nylon  |
| Tile Dimensions            | 50cm x 50cm  |
| Pile Weight                | 975g/m <sup>2</sup> +/-10%   |
| Total Weight               | 4200g/m <sup>2</sup> +/-10%  |
| Total Thickness            | 7.8mm +/-10%   |
| Backing Description        | Bitumen composite, 70% recycled  |
| Flammability               | Euroclass Bfl-s1   |
| Castor Chair Rating        | BS EN 985 Pass - suitable for continuous use   |
| Static Loading             | BS 4939:1987 (2003) Recovery >80% (24hrs)  |
| Dynamic Loading            | BS ISO 2094:1999 (2005) Loss <20% (1000 impacts)                                       |
| Body Voltage Test          | BS ISO 6356:2000 <2kV  |
| Colour Fastness To Light   | BS EN ISO 105 - B02 Minimum grade 6  |
| Colour Fastness To Shampoo | BS 1006:UK-TB: 1990 Minimum grade 4  |
| Number of Tiles per Box    | 20   |
| BREEAM RATING              | For specific ratings, please refer to <a href="http://www.bre.co.uk">www.bre.co.uk</a> |



L p g b ?

|                              |  |
|------------------------------|--|
| Product Name                 | 4400 Broadway  |
| Product Description          | Heavy Contract Carpet  |
| Pile Yarn Description        | 85% Polypropylene 15% Nylon  |
| Roll Length                  | 30m  |
| Roll Width                   | 2m   |
| Total Weight                 | 975g/m <sup>2</sup> +/-10%   |
| Total Thickness              | 6.5mm +/-10%   |
| Flammability                 | Euroclass Efl-s1*  |
| Castor Chair Rating          | BS EN 985 Pass - suitable for continuous use   |
| Static Loading               | BS 4939:1987 (2003) Recovery >80% (24hrs)  |
| Dynamic Loading              | BS ISO 2094:1999 (2005) Loss <20% (1000 impacts)                                       |
| Body Voltage Test            | BS ISO 6356:2000 <2kV  |
| Colour Fastness To Light     | BS EN ISO 105 - B02 Minimum grade 6  |
| Colour Fastness To Shampoo   | BS 1006:UK-TB: 1990 Minimum grade 4  |
| Sound Absorption Coefficient | BS EN 354:2003   |
| Reduction in Impact Noise    | BS EN 140-8: Part 8: 1998 19dB   |
| BREEAM RATING                | For specific ratings, please refer to <a href="http://www.bre.co.uk">www.bre.co.uk</a> |

\*200m2 minimum order quantity for Cfl-s1 rating



L p s q g b ?

**Burmatex Ltd,**  
Victoria Mills, The Green,  
Ossett, West Yorkshire  
WF5 OAN, United Kingdom

T +44 (0) 1924 262 525  
F +44 (0) 1924 280 033  
UK email: [projects@burmatex.co.uk](mailto:projects@burmatex.co.uk)  
International email: [international@burmatex.co.uk](mailto:international@burmatex.co.uk)  
[www.burmatex.co.uk](http://www.burmatex.co.uk)

Burmatex reserve the right to improve the specification of all products without prior notification. E&OE