

# "EXTELINE" TACTILE TILE WHITE 42X84 CM Ref. 4220

## Technical Data Sheet - GB









Railway platform edge

Complies with standard NFP 98351

- Tactile and visual device intended for alerting blind and partially sighted people to imminent dangers on their way like:
  - · Road crossing
  - · Railway platform edge
  - Bus stop
  - Stairs...
- Made of fiber-reinforced methacrylate resin, the tile is:
  - · Extremely flexible
  - · Does not turn yellow with UV light
  - Extremely tear-resistant
  - Easy to install
  - Extraordinarily anti-slip (even wet)
  - · and hard to get dirty.

#### Bonding system:

Recommended for outdoor and indoor use on surface media which are:

#### Coated:

The surface should be clean, dry and free of non-adherent material (dust, grit, grease, oil, etc.). New coatings should be at least 1 month old and be free of bleeding dye for their application.

#### Concrete:

After making sure that the surface is clean, dry and free of non-adherent material (dust, grit, grease, oil, etc.). For new screed let dry for at least 3 weeks.

- 1 Blast it or diamond grind it.
- 2 Apply a layer of **MTA PRIMER (methacrylate Ref. 4228)** with a roller (about 400g / m²).

### "EXTELINE" TACTILE TILE WHITE 42X84 CM Ref. 4220

## Technical Data Sheet - GB

#### Stages for applying the tile:

- 1) Establish and define the application area on your surface media with masking.
- 2) Mix the two components of the MTA glue (methacrylate ref 4229), using an electric mixer.
- **3) Apply** the mixture with a notched trowel (B15 Ref. 94919 with teeth 4 mm wide by 2.5 mm high).

For more open surfaces it is advisable to use a trowel (with teeth 7 mm wide by 5 mm high) in the amount of:

- For the "EXTELINE" TACTILE TILE 42 x 84: 1 to 3 kg/tile depending on the surface media.

Pass the mixture about 5 mm over your masking.

- **4) Place** immediately the "EXTELINE" TACTILE TILE on the glue. Apply some light pressure to avoid air bubbles and to spread glue to edges and corners.
- **5) Remove** the masking and wait for it to fully harden before allowing pedestrian traffic.



MATERIAL	Colour	420 x 840 mm
Methacrylate	White	4220

	Architect/Investor:			
	Project:			
	Email:			
	Tel:			
	Distributor:	Tel:	Email:	
١				